Approved For Release 2000/09/11 : CIA-RDP80-00809A000500450230-4 U.S. Officials Only CONFIDENTIAL CENTRAL INTELLIGENCE AGENCY 25X1A INFORMATION REPORT COUNTRY Poland SUBJECT Huta Poloj Steel Plant 25X1A PLACE ACQUIRED (BY SOURCE) OCI NO. DATE ACQUIRED (BY SOURCE) DATE DISTR. /9 Apr 1954 DATE (OF INFO.) 1939 and 1953 25X1X 1. The Huta Poloj stree plant is located in the town of Nowy Bytom about 10 miles north east of Katowice. It is entirely a company town with the steel plant the only industry. The plant consists of: a. Coke Ovens b. Chemical Plant c. Six Blast Furneces - Capacity 400/500 MTs/Day each. d. Seven Open Hearth Furnaces - Largest 100 Ts, Day, Smallest hOTs/Day. e. Blooming Mill 32" Diam. f. Reil Mill g. Reversible Will - (Ctructural steel, 30 cm. beam is largest which can be rolled) h. Plate mill - Leximum width two ms. Maximum thickness 25 mm. 1. Sheet Mill - 13 mills with capacity of 3000 MTs per month. j. Forge - Five nammers: 10Ts, 12Ts, 5Ts and smaller k. Structural Chop for fabricating building frames. 1. Machine Shop . For internal repairs and manufacturing wheels and axles. m. Sendzimir Mill for manufacture of sheet for tinning. n. 22,000 KW power plant. have been entirely rebuilt cince World War II and the machine shop has been re-equipped with new modern machine tools. The plant was not damaged during the 3. The total output of the plant was 250,000 tons of finished steel products per The major output of steel was rails and accessories. Most of the wheels and axles

DISTRICUTION STATE ARMY NAVY AIR FOI

This report is for the use within the USA of the Intelligence components of the Departments or

U.S. Officials Only CONFIDENTIAL

manufactured were shipped to USER before World War II.

This report is for the use within the USA of the Intelligence components of the Departments or Agencies indicated above. It is not to be transmitted overseas without the concurrence of the originating office through the Assistant Director of the Office of Collection and Dissemination. CIA.

## Approved For Release 2000/09/11: CIA-RDP80-00809A000500450230-4

Page 2 CUNFIDENTIAL UF OFFICIAL ONLY



- 4. There was a considerable production of chemicals from coke and a large production of phosphate fertilizers. These fertilizers were made largely from open hearth slags. About 30 percent of ore was from the company's own mines. It 25X1X contained from two to four percent phosphorus, not high enough for Thomas furnace use. The balance of ore formerly came from the 3 R and later from Morocco 25X1X and Sweden. The process for utilizing the phosphorus from the slag of these ores to make fertilizer and developed at the plant and proved very successful.
- 5. The coal used Was obtained from two neighboring mine, and was shipped by serial tram to the trant at the rate of 2000 tone per day. This coal had inferior ocking qualities and a great deal of difficulty was found in using it at first. Later a patented mathod was developed at the plant and excellent coke was ultimately produced.
- 6. About 7000 man werd employed plus some 380 engineers. They were housed (n company c.s. I homes adjoining the plant.
- 7. On the Sendsimer Mill erected at Huta Yoloj was the first of several later created in France and the d.S. The one at Huta Poloj after a difficult year of trial and error ultimately was very successful and steedily produced an average of 30 MT- of tin sheet, varying slightly sith thickness.
  - b. There was only one stand creeted. Its major differences with previous rolling methods was that the rolls were only from one to two inches in diameter. They were driven by larger rolls or series of rolls which were entased in housings and could transmit a high pressure to the small rolls. The bight they could take was much greater than with common rolls and there was a tension applied to the billet being rolled so that it was in tension as well as compression while passing through the rolls. The method used at first was to pass the material in a continuous band for 13 to 15 passes; the extension of length being taken care of by passing the band being rolled over pulleys, one of which was mounted on a car which moved on a track as the length increased. A later improvement involved winding the material on a model or winder. The width of the finished sheet was governed by USSR specifications, 711 mms. In the US at is now two meters.

- end ..

ENCLOSURE (A): Diagram of Huta Poloj Steel Plant

## LIBRARY SUBJECT & AREA CODES

1-6/740.1 55% 4-5/733.9 55% 4-12/740.1 55% 2-12/733.92 55%

CONFIDENTIAL
US OFFICIALS ONLY

## Approved For Release 2000/09/11: CIA-RDP80-00809A000500450230-4 25X1A CONFIDENTIAL ENCLOSURE (A) US OFFICIALS DNLY DIAGRAM OF HUTA POLOJ STEEL PLANT Narrow Gauge Coal Railroad Slag Dumps Area 3000x 3000 ms ± Street Niedurnego 7 8 10 Bath House 2. Sheet Shop 13 (res places 12 3. Structural Shop 4. Blast Furnaces 5. Boiler House 6. Cuke Ovens 7. Rolling Mills Staff Houses Park 8. Power Pouse 9. Machine Shop 10. Warehouses 11. Managers Home 12. Post Office 13. Hospital ? 14. Workers Club HUTA POLOJ, STEEL PLANT Worker; Nowy Bytom, Poland Not to scale -end-CONFIDENTIAL/US OFFICIALS ONLY